



A-Z IZOLIME

PRODUKT- KATALOG



A-Z IZOLIME

+383 48 158 592

info@az-izolime.com

Rr. Pjetër Hasanaj p.n.

50000 Gjakovë, Republika e Kosovës



A-Z IZOLIME



A-Z IZOLIME

Technische Eigenschaften

GURI Steinwolle Schale ALU

Brandverhalten	A1
Brandverhaltensgruppe	RF1
Wärmeleitfähigkeit	λ_D W/mK 0.040
Anwendungstemperatur	bis zu +650 °C
Volumengewicht	≤ 80 kg/m ³

Rohr \varnothing	Dämmstärke							
	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm		
18	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm		
22	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm		
28	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm		
35	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm		
42	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm		
48	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm	
54	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm	120 mm
60	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm	120 mm
64	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm	120 mm
76	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm	120 mm
89	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm	120 mm
108	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm	120 mm
110		30 mm	40 mm	50 mm	60 mm	80 mm	100 mm	120 mm
114		30 mm	40 mm	50 mm	60 mm	80 mm	100 mm	120 mm
133		30 mm	40 mm	50 mm	60 mm	80 mm	100 mm	120 mm
140		30 mm	40 mm	50 mm	60 mm	80 mm	100 mm	120 mm
159		30 mm	40 mm	50 mm	60 mm	80 mm	100 mm	120 mm
168		30 mm	40 mm	50 mm	60 mm	80 mm	100 mm	120 mm
219		30 mm	40 mm	50 mm	60 mm	80 mm	100 mm	120 mm



A-Z IZOLIME



A-Z IZOLIME

Technische Eigenschaften

GURI Steinwolle Schale

Brandverhalten	A1
Brandverhaltensgruppe	RF1
Wärmeleitfähigkeit	λ_D W/mK 0.040
Anwendungstemperatur	bis zu +650 °C
Volumengewicht	≤ 80 kg/m ³

Rohr \varnothing	Dämmstärke							
	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm		
18	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm		
22	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm		
28	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm		
35	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm		
42	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm		
48	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm	
54	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm	120 mm
60	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm	120 mm
64	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm	120 mm
76	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm	120 mm
89	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm	120 mm
108	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm	120 mm
110		30 mm	40 mm	50 mm	60 mm	80 mm	100 mm	120 mm
114		30 mm	40 mm	50 mm	60 mm	80 mm	100 mm	120 mm
133		30 mm	40 mm	50 mm	60 mm	80 mm	100 mm	120 mm
140		30 mm	40 mm	50 mm	60 mm	80 mm	100 mm	120 mm
159		30 mm	40 mm	50 mm	60 mm	80 mm	100 mm	120 mm
168		30 mm	40 mm	50 mm	60 mm	80 mm	100 mm	120 mm
219		30 mm	40 mm	50 mm	60 mm	80 mm	100 mm	120 mm



A-Z IZOLIME



Technische Eigenschaften

GURI Steinwolle Bogen

Brandverhalten	A1
Brandverhaltensgruppe	RF1
Wärmeleitfähigkeit	λ_D W/mK 0.040
Anwendungstemperatur	bis zu +650 °C
Volumengewicht	≤ 80 kg/m ³

Rohr \varnothing	Dämmstärke							
	30 mm	40 mm	50 mm	60 mm	80 mm			
18								
22								
28								
35								
38								
42								
44								
48								
54								
57								
60								
64								
67								
70								
76							100 mm	
89							100 mm	
102							100 mm	
108							100 mm	
110							100 mm	
114							100 mm	120 mm
133							100 mm	120 mm
140							100 mm	120 mm
159							100 mm	120 mm
168							100 mm	120 mm
194							100 mm	120 mm
219							100 mm	120 mm



A-Z IZOLIME



Technische Eigenschaften

ISO PIR Schale ALU

Wärmeleitfähigkeit	λ D W/mK 0.027
Anwendungstemperatur	-40°C bis zu +120 °C
Volumengewicht	ca. 33 kg/m ³

Rohr \varnothing	Dämmstärke						
	20 mm	30 mm	40 mm	50 mm	60 mm		
12	20 mm	30 mm	40 mm	50 mm			
15	20 mm	30 mm	40 mm	50 mm			
17	20 mm	30 mm	40 mm	50 mm	60 mm		
18	20 mm	30 mm	40 mm	50 mm	60 mm		
21	20 mm	30 mm	40 mm	50 mm	60 mm		
22	20 mm	30 mm	40 mm	50 mm	60 mm		
24	20 mm	30 mm	40 mm	50 mm	60 mm		
25	20 mm	30 mm	40 mm	50 mm	60 mm		
26	20 mm	30 mm	40 mm	50 mm	60 mm		
28	20 mm	30 mm	40 mm	50 mm	60 mm		
30	20 mm	30 mm	40 mm	50 mm	60 mm		
32	20 mm	30 mm	40 mm	50 mm	60 mm		
33	20 mm	30 mm	40 mm	50 mm	60 mm		
35	20 mm	30 mm	40 mm	50 mm	60 mm		
40	20 mm	30 mm	40 mm	50 mm	60 mm		
42	20 mm	30 mm	40 mm	50 mm	60 mm		
44	20 mm	30 mm	40 mm	50 mm	60 mm		
48	20 mm	30 mm	40 mm	50 mm	60 mm		
50	20 mm	30 mm	40 mm	50 mm	60 mm		
51	20 mm	30 mm	40 mm	50 mm	60 mm		
52	20 mm	30 mm	40 mm	50 mm	60 mm		
54	20 mm	30 mm	40 mm	50 mm	60 mm		
57	20 mm	30 mm	40 mm	50 mm	60 mm		
60	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
64	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
70	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
76	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
83	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
89	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	

90	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
95	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
102	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
108	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
110	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
114	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
117	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
121	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
127	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
133	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
136	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
140	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
144	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
152	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
159	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
160	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
168	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
219	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
273	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
324	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm



A-Z IZOLIME



Technische Eigenschaften

ISO PIR Schale

Wärmeleitfähigkeit λ_D W/mK 0.027
 Anwendungstemperatur -40°C bis zu +120 °C
 Volumengewicht ca. 33 kg/m³

Rohr \varnothing	Dämmstärke						
12	20 mm	30 mm	40 mm	50 mm			
15	20 mm	30 mm	40 mm	50 mm			
17	20 mm	30 mm	40 mm	50 mm	60 mm		
18	20 mm	30 mm	40 mm	50 mm	60 mm		
21	20 mm	30 mm	40 mm	50 mm	60 mm		
22	20 mm	30 mm	40 mm	50 mm	60 mm		
24	20 mm	30 mm	40 mm	50 mm	60 mm		
25	20 mm	30 mm	40 mm	50 mm	60 mm		
26	20 mm	30 mm	40 mm	50 mm	60 mm		
28	20 mm	30 mm	40 mm	50 mm	60 mm		
30	20 mm	30 mm	40 mm	50 mm	60 mm		
32	20 mm	30 mm	40 mm	50 mm	60 mm		
33	20 mm	30 mm	40 mm	50 mm	60 mm		
35	20 mm	30 mm	40 mm	50 mm	60 mm		
40	20 mm	30 mm	40 mm	50 mm	60 mm		
42	20 mm	30 mm	40 mm	50 mm	60 mm		
44	20 mm	30 mm	40 mm	50 mm	60 mm		
48	20 mm	30 mm	40 mm	50 mm	60 mm		
50	20 mm	30 mm	40 mm	50 mm	60 mm		
51	20 mm	30 mm	40 mm	50 mm	60 mm		
52	20 mm	30 mm	40 mm	50 mm	60 mm		
54	20 mm	30 mm	40 mm	50 mm	60 mm		
57	20 mm	30 mm	40 mm	50 mm	60 mm		
60	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
64	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
70	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
76	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
83	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
89	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	

90	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
95	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
102	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
108	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
110	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
114	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
117	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
121	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
127	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
133	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
136	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
140	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
144	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
152	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
159	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
160	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
168	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
219	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
273	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
324	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm



A-Z IZOLIME



Technische Eigenschaften

ISO PIR Bogen

Wärmeleitfähigkeit	λ_D W/mK 0.027
Anwendungstemperatur	-40 bis zu +120 °C
Volumengewicht	ca. 33 kg/m ³

Rohr \varnothing	Dämmstärke						
15	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
18	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
22	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
28	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
35	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
42	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
48	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
54	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
60	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
64	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
76	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
89	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
108	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
110	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	
114	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
127	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
133	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
140	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
159	20 mm	30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
168		30 mm	40 mm	50 mm	60 mm	80 mm	100 mm
219		30 mm	40 mm	50 mm	60 mm	80 mm	100 mm